

# Precoating



By forming PTFE precoated fine wires, fully coated each filar add excellent lubricity to both inside and outside of cable without losing the property of the cable. This processing applied to one layer hollow cable like ACT ONE or Wire coil. Ideal for applications requires lubricity and chemical resistance in addition to the property of the hollow cable like 1 to1 Torque response and flexibility.















## Specifications

Min. coating thickness	0.01 mm
Coating material	PTFE
Length	up to 1500mm
End treatment	Grind or manual cut (EDM cut is not available)
Available for	ACT ONE, Wire coil

# Product lineup

## Specifications and Comparison of properties

Legend : 5=Highest, 1=Lowest applicability

Category	Item	Type	Specification(Trial)		1to1 Torque response	High-speed rotation	Push/Pull	Compression	Flexibility	Feature
			OD(mm)	ID(mm)						
Hollow cable	Torque coil	 3layer 2layer flat auger*	0.36-6.00 0.30-5.17 - -	0.18-3.20 0.15-3.20 - -	5	5	3	2	4	bi-directional (3 layers) or unidirectional (2 layers) rotation *Archimedes screw with spiral wire
	Torque Hypotube		0.20-1.10	0.10-0.70	5	2	5	5	1	high breaking strength and elongation resistance
	ACT ONE	 standard flat ultra thin auger*	0.21-4.52 0.21-4.52 0.42-3.75 -	0.13-3.20 0.16-3.20 0.34-3.20 -	4	3	4	3	3	well balanced properties *Archimedes screw with spiral wire
	Wire coil	 round flat	0.10-3.50 0.10-5.90	~1.80 0.07-5.30	1	1	2	4	5	high flexibility and compression resistance
Cable	Drive Cable	 2-6layer	0.41-6.00	-	5	5	5	4	2	Optimized for high speed rotation and power transmission
	Torque rope	 1x3,1x7, 1x12,1x19	0.30-3.00	-	4	3	5	4	3	1:1 torque transmission at hand-speed rotation
	Wire rope	 1x7,1x19 7x7,7x19 7x7x7, etc.	0.09-3.00	-	1	1	5	4	3	High breaking strength and elongation resistance
Coating	Outer coating	 Extrusion Dip coat Spray	Floropolymer Nylon, etc.							To add lubricity, ablation resistance or biocompatible sealing to cable
	Inner tube		Floropolymer							Inner coating applied to a hollow cable
	Precoating		PTFE							Coating for both inner and outer of hollow cable without losing the property of the cable
Assembly	Machining & Assembly	 Laser welding, Grinding Tube assembly								Variety of welding and machining available for assembly or additional mechanical property
	End termination	 Ball, Eye, Loop, etc.								For the end of a cable or used for intermediate attaching.
Power transmission	Synchromesh wire rope	 AWS40 -AWS120	1.10-3.40	-						Synchronous round belt, ideal for linear-motion system drawn in 3-dimensional.
	Cable rack	 CL0.8S / H	W3.0 x H3.6	-						With stainless cable core, ideal when the Rack needs to be flexible and high-force movement required.

# ACT ONE®



ACT ONE cable tubes possess a high maximum torque and high torque transmission compared to polymer braided tubes. They also feature higher kink resistance and flexibility compared to hypo tubes. ACT ONE cable tubes are applied to a wide variety of minimally invasive and interventional devices within Cardiology, Peripheral, Neurology, Oncology, Orthopedics, and Endoscopy.

## Specifications

Type		1to1 Torque Response	Pushability	Flexibility	OD	ID	Filar*	Length
Standard		5	3	5	0.27-2.80 mm (Trial : 0.21-4.52)	0.16-2.10 mm (Trial : 0.13-3.20)	6-18	up to 3000mm
Flat		4	3	4	0.66-1.57 mm (Trial : 0.21-4.52)	0.44-1.27 mm (Trial : 0.16-3.20)	8-18	up to 3000mm
Swage		4	5	2	0.71-2.46 mm (Trial : 0.39-3.83)	0.45-1.81 mm (Trial : 0.21-3.10)	7-18	up to 3000mm
Ultra Thin		1	1	5	0.50-3.03 mm (Trial : 0.42-3.75)	0.13-2.75 mm (Trial : 0.34-3.20)	2-12	up to 3000mm
Auger		2	3	5	Above ACT ONE with spiral wire, used as Archimedes screw (Japan Patent number : 5408809)			

\*By changing the number of filars, the flexibility of ACT ONE can be customized.

"ACT ONE" is registered trademarks of ASAHI INTECC CO., LTD.

**Legend** 5 = Highest applicability  
1 = Lowest applicability